



SODEMACO



Name	13-4 General Light SupraCoat	Article number	13-4GLSC	EN388  4542 CE CAT II
Colour	Grey / Grey	Glove thickness	Palm: 1,2 mm Back of hand: 1,0 mm	
Size	7-11	Packaging	6 pairs / plastic bag, 60 pairs / carton	
Certification number	LPMPPZ 2015-1667	Barcode	7: 7340022526229, 8: 7340022526236, 9: 7340022526243 10: 7340022526250, 11: 7340022526267	

Glove purpose	Designed for high dexterity and moderate cut resistance
Materials	Liner in Polyamide, SupraBlock Cut and glass fibre Coating in SupraCoat; PU and Nitrile foam.
Fitting (elastic tight, tight, close, loose)	Tight fit.
Abrasion	Very good abrasion resistance.
Cut	Cut resistance is provided by high strength and high hardness. Strength ●●●○○ Hardness ●●●●○
Tear	High tear resistance makes the glove dangerous for entangling.
Puncture	Poor puncture and needle resistant.
Heat and insulation	Not suitable for contact with heated objects. Not suitable for use in cold temperatures.
Water/Oil	Not water / oil resistant. Coating has moderate resistance to organic solvents and hydrolysis.
Grip	Very good dry and wet grip.
Breathing	Very good breathing properties.
Impact	No impact protection.
Chemical safety	REACH safe. Does contain small amount of zinc organic accelerators. The cuff elastic band does contain very small amount of latex covered by polyester.

Disposal	No special waste	Storage and cleaning notice	Wash in 30 degrees.
Suitable industries	Fine risky assembly tasks, light mechanical industry.		Store in cool, dry and dark place. Avoid storage for several years.