

Zwaluw Rust Primer Red Brown

Alkyd-resin-based, fast-drying



Product Description

Zwaluw Rust Primer Red is a fast drying corrosion protection primer. It has excellent rust protection abilities.

Benefits

Applications

Directions Of Use

All surfaces must be dry, clean and free of dirt or corrosion. Surfaces should have room-temperature, if possible. Shake can vigorously for approx. 3 min as soon as the mixing balls are audible. Apply cross-wise in several coats with a distance of approx. 15-20 cm.

Additional information

Application temperature	+16°C to +25°C
Base	Alkyd-resin
Curing time	24 hours
Density	0.824
Dust free after min	70
Extrusion rate gs	1.5
Film thickness coverage_m	50
Frost resistance during transportation	Up to -15°C
Pressure at 20c bar	3.7
Pressure at 50c bar	7.3
Re-coatable after hrs	24
Solid contents	23.8
Tack free time	35-40 minutes
Temperature range_c	-25°C to +80°C

These are typical values

Limitations

Surface Preparations and Finishing

Surfaces must be clean, dry and free of grease, rust and loose particles.

Paintability

Paintable with most lacquers and paints, test prior to application.

Cleaning

Colour(s)

- Red Brown

Packaging

- Can

For product specifications, please refer to the Product Detail Page